

Under-Cabinet

CORTEO

The sleek shape of Corteo makes it a perfect companion for today's modern kitchens. Advanced features like the quiet Captur[™] system and LED lighting make it a pleasure to use. The LED modules included with this hood are the latest in LED cooktop illumination technology specially designed to operate in the elevated temperatures of cooking - offering bright lighting and lasting up to 25 times as long as a standard bulb and greater reliability than typical replacement LED bulbs.

SIZE	WHITE	BLACK	STAINLES		ASE FILTE		NON-DUCTED FILTER(S)	
30 in. CRSF130WW		CRSF130BI	_ CRSF130S	S HPF	S HPFA130 (Type C		PF30 (Type X	
					<u></u> _			
PERFOR				-			- N 4	
Duct	Orientation	Size	Damper	Sones		CFM		
\ /o mti l	Destancular	01/ in 10 !	Included	Normal	High	Normal	High	
	Rectangular I - Rectangular	3¼ in. x 10 in. 3¼ in. x 10 in.	Included	1.5 1.5	5.0 5.0	140	230 210	
Round - V	<u> </u>	7 in.	Sold Separately	1.5	5.0	110 150	210	
Rouna -	vertical	/ 111.	Solu Separately	1.5	5.0	150	200	
FEATUR	ES							
Control ty	/pe	2-speed Rocker						
) -		no						
Filter Clean Reminder		no						
Heat Ser	ntry™	no						
ADA Cap	able	yes		1				
Lighting		1-level LED (included)]				
Grease F	ilters	Open Mesh (Qty. 2)]				
Installatio	n Hardware	EZ1 brackets						
ENERGY	′ STAR®	no]				
Recircula	tion	Non-ducted filte	rs sold separately				/	
AC INPU	IT			21				
120 V, 6	0 Hz - 0.65 AM	PS]		\leq		
OPTION	AL ACCESSOF	RIES						
7-in. Rou	ind Damper	BP87Q]			I	
Make-up	Air Dampers	MD6TU, MD8TI	J and MD10TU]			and the second se	
MOUNTI	NG HEIGHT							
18 in. to	24 in. from coo	ktop to bottom o	f hood]				
LIMITED	WARRANTY							
1-year				1				
	ED modules on						\frown	
		or full warranty te	ext.			~ /		
	OOR USE ON	LY				`/_/	\sim	
0.5			Vertical High Speed,					
0.4 مَ			 7-in. round Vertical High Speed, 	f	\swarrow	\sim		
0.3			with 3¼ in. x 10 in. dam	per L		· 1710		
			 Horizontal High Speed, with 3¼ in. x 10 in. dam 					
0.3			with 3% in. x 10 in. dam				298	
0.1					_ 2۱	- Á	258	
					.1	\searrow		
0	50 100	150 200	250 300	350		¥		



Airflow (cfm)

HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-theshelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

SPECIFICATION SHEET CORTEO - CRSF1 SERIES