BRSAN

SPECIFICATION SHEET

AUTOMATIC MAKE-UP AIR DAMPER

Broan's Automatic Make-up Air Damper provides interlocked damper operation so outside air is only allowed to enter the house when a connected fan or hood is operating.

Model MD6T (for 6" round duct) Model MD8T (for 8" round duct) Model MD10T (for 10" round duct)

- 24 Volt, 60 Hz AC motor
- Normally closed damper
- Automatically opens when exhaust fans are activated
- Foam seals minimize air leakage
- 24 gauge galvanized steel construction
- Damper adjustment screw for balancing adjustments
- Compatible with select Broan and BEST range hoods
- Use with Fresh Air Inlet Model 641FA for 6" dampers, Fresh Air Inlet Model 643FA for 8" dampers or Fresh Air Inlet Model 610FA for 10" dampers (sold separately)
- Includes 24 Volt 20VA transformer

Model SMD6 (for 6" round duct) Model SMD8 (for 8" round duct)

- Same features as Model MD6T and Model MD8T except includes LinkLogic relay
- Compatible with Broan fans and BEST range hoods equipped with LinkLogic devices
- Requires no special wiring to range hoods or fan enabled with LinkLogic^{*}. Communicates over existing power lines
- LinkLogic[®] relay fits single-gang box









LinkLogic[®] Relay SMD6 & SMD8 only

Model MD10T

Transformer Included with all models

Broan-NuTone LLC Hartford, Wisconsin www.broan.com 800-558-1711				
REFERENCE	QTY.	REMARKS	Project	
			Location	
			Architect	
			Engineer	
			Contractor	
			Submitted by	Date