


FRESH AIR SYSTEMS BETTER AIR. BETTER LIFE.

HEAT RECOVERY VENTILATORS



FRESH AIR, WHEREVER YOU LIVE.

For today's tightly constructed, energy efficient homes, Broan Heat Recovery Ventilators (HRVs) continuously supply fresh air to improve indoor air quality in every season. These fresh air systems exchange stale indoor air and pollutants with fresh, filtered outside air and Venmar[®] Core Technology tempers incoming air to help maintain optimal indoor temperature levels. The result-fresh air in your home, all year long.

	HE SERIES			A				
Model Name	HRV160 ECM	HRV200 ECM	HRV250 ECM	HRVH100	HRV150	HRV130FL		
Model Number	HRV160TE	HRV200TE	HRV250TE	HRVH100S	HRV150S	HRV130FLS		
Min/max continuous airflow (CFM at 0.2 in. w.g.)	53–177	50-245	50-271	50-112	66-174	_		
Min/max continuous airflow (CFM at 0.4 in. w.g.)	53-156	50-226	50-250	50-104	66-150	66-129		
Fan efficacy at 32°F (CFM/Watt)	2.0	3.4	3.6	1.2	1.2	1.0		
Apparent sensible efficiency at 32°F $^{\rm 1}$	83%	85%	81%	75%	79%	83%		
Sensible recovery efficiency at 32°F $^{\!\!1}$	75%	80%	75%	65%	67%	75%		
Sensible recovery efficiency at -13°F ¹	64%	73%	66%	60%	60%	60%		
Total recovery efficiency at 95°F 1	-	_	_	-	_	-		
Filtration level	MERV 9	MERV 6 / HEPA option	MERV 6 / HEPA option	HEPA	15 PPI	MERV 6 / MERV 8 option		
Filter model number	SV18205	SV63426 / 21996	SV63426 / 21996	ACCHEPARF + ACCHEPAPFK	SV60800	V65683		
ENERGY STAR [®] Certified ³	Yes	Yes	Yes	Yes	Yes	Yes		
Ports location	Тор	Тор	Тор	Side	Side	Side		
Ports size (in.)	6	6	6	5	6	5		
Dimensions (in.) H x W x D								
Side port	—	_	_	17 x 39 x 12	17 x 35 x 17 ¹ /4	22 ⁹ / ₁₆ x 22 ¹ / ₁₆ x 13 ⁷ / ₈		
Top port	24 ⁹ / ₁₈ × 23 ⁹ / ₁₈ × 14 ¹⁵ / ₁₆	31 x 32 x 20		_	_	-		
Weight (lbs)	52	82	81	46.5	65	47		
Warranty on parts	5 years	5 years	5 years	5 years	5 years	5 years		
Warranty on core	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime		

¹Performance at low speed. ²Based on the latent recovery performance of the Broan ERV100 model.



³This product earned the ENERGY STAR rating by meeting strict energy efficiency guidelines set by Natural Resources Canada and the U.S. EPA. It meets ENERGY STAR requirements only when used in Canada.

MANAGE TEMPERATURE IN EVERY SEASON

HEATING SEASON	Minneapolis, Minn	esota COOLING	SEASON P	Phoenix, Arizona
Outside air to house -13°F 7°F Stale air to outside	Stale a building Pretreate to house	g 75°F 105°F Stale to outside d air		Stale air from building 75°F Pretreated air to house 83°F ²
ADVANCED			COMPACT FLEX [™] SERIES	
HRV190	HRV160	HRV80	HRV90	HRV120
HRV190S	HRV160T	HRV80S / HRV80T	HRV90S / HRV90T	HRV120S / HRV120T
82-215	65-183	37-86	47-95	64-126
82-192	65–155	37-77	47-90	64–115
1.2	1.3	1.2	1.2	1.2
75%	83%	80%	75%	74%
65%	75%	68%	66%	65%
60%	72%	60%	60%	60%
_	_	_	_	_
15 PPI	MERV 7	30 PPI	30 PPI	30 PPI
SV60800	SV18204	SV18883	SV18883	SV16032
Yes	Yes	Yes	Yes	Yes
Side	Тор	Side / Top	Side / Top	Side / Top
6	6	4	4	5
17 x 35 x 17 ¹ /4	_	16 ⁵ /16 × 19	1 ¹³ / ₁₆ × 15 ⁵ / ₈	21 ³ /16 × 27 ¹ /16 × 19 ¹³ /16
_	$24^{9}/_{16} \times 24^{9}/_{16} \times 14^{15}/_{16}$	18 ⁵ /8 × 15	5 ⁷ /16 × 15 ⁵ /8	16 ¹ / ₄ x 23 ⁵ / ₈ x 19 ¹³ / ₁₆
65	52	30	30	42
5 years	5 years	5 years	5 years	5 years
Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime	Limited lifetime

Residential Main Wall Controls

Broan offers simple to more advanced wall controls to customize your fresh air system.

Auxiliary Wall Controls provide additional control:

VB20W Bathroom override 20-minute timer

VB60W Bathroom override 20/40/60-minute timer



SELECT THE WALL CONTROL BEST SUITED TO YOUR NEEDS

Main Wall Controls							Auxiliary	
Model	VT4W	VT6W	VT7W	VT8W	VT9W	VB20W	VB60W	
HRV80	•	•	•	•		•	•	
HRV90	•	•	•	•		•	•	
HRVH100	•	•	•	•		•	•	
HRV120	•	•	•	•		•		
HRV150	•	•	•			•		
HRV160	•	•	•	•		•	•	
HRV160 ECM			•	•		•	•	
HRV190	•	•	•			•		
HRV200 ECM					•	•	•	
HRV250 ECM					•	•	•	

Main Wall Control Features

	VT4W	VT6W	VT7W	VT8W	VT9W
Continuous minimum speed	•	•	•	•	•
Continuous maximum speed	•	•	•	•	•
Dehumidistat		•	•		•
Intermittent: 20 minutes/hour	•		•	•	•
Turbo: Maximum speed for 4 hours					•
Recirculation			•	•	•
Smart				•	•
Program				•	
Electronic balancing					•

ACCESSORIES See the complete line at www.broan.com

WHISPER REGISTERS

Model V01269

• 4" intake and exhaust

Model V02863 · 5" intake and exhaust

Model V01271

• 6" intake and exhaust

- Model V03585
- 8" intake and exhaust



· Roof cap up to 6"

GRILLES/PLASTIC REGISTERS

Model V04790 Duct connector baffle

8" x 12"

Model V04400 Duct connector 8" x 12"



· Balancing kit 0.5" and 1" H2O

Model 18222



Model V11001

AIRFLOW BALANCING KITS

· Airflow collar 6"d

Model V11246

Model V11247 • Airflow collar 7"d



Broan.com

Broan-NuTone LLC, 926 W. State Street Hartford, WI 53027 800-558-1711

America's Choice For Green Builders.[®] Proud to be ENERGY STAR[®] partners.



EXTERIOR VENTS

Tandem transition

Model VTYIK1

[·] Airflow collar 8"d