

SIZE	STAINLESS	GREASE FILTERS (replacement)	NON-DUCTED FILTERS		
30 in.	BPDP130SS	HPFA424 (Type "B5")	HPF24 (Type "Xb")		
36 in.	BPDP136SS	HPFA430 (Type "C5")	HPF30 (Type "Xc")		
42 in.	BPDP142SS	HPFA436 (Type "D5") HPF36 (Type "Xd")			
48 in.	BPDP148SS	HPFA442 (Type "E5")	HPF42 (Type "Xe")		

PERFORMANCE								
Duct Orientation	Size	Damper	Sones		CFM			
Duct Orientation			Normal	High	Normal	High		
Vertical - Rectangular	3¼ in. x 10 in.	Included	0.5	6.0	150	390		
Horizontal - Rectangular	3¼ in. x 10 in.	Included	0.6	5.5	150	400		
Round - Vertical	7 in.	Sold Separately	0.4	5.5	150	390		

FEATURES				
Control type	2-speed Deluxe Rocker			
Delay off	no			
Filter Clean Reminder	no			
Heat Sentry™	no			
ADA Capable	yes			
Lighting	1-level LED (included)			
Grease Filters	Hybrid Baffle (Qty. 2)			
Installation Hardware	EZ1 brackets			
ENERGY STAR®	no			
Recirculation	Non-ducted filters sold separately			
AC INPUT				
120 V, 60 Hz - 1.4 AMPS				
OPTIONAL ACCESS	ORIES			
7-in. Round Damper	BP87Q			
Make-up Air Dampers	MD6TU, MD8TU and MD10TU			
MOUNTING HEIGHT				
18 in. to 30 in. from cooktop to bottom of hood				
LIMITED WARRANTY	,			
1-year 3-year (LED modules <i>(See installation manu</i>	only) al for full warranty text.)			





Under-Cabinet

SPIRE





HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

