BRGAN NuTone

SPECIFICATION SHEET

MODEL PM390 POWER PACK

FEATURES

- Multi speed control
- Centrifugal blower, 390 CFM, 6.0 Sones
- 6" round duct connector/backdraft damper
- Enclosed light
- Accepts two incandescent max. 40-watt candelabra bulb (not included)
- One piece washable aluminum mesh filter
- Durable, powder coated silver finish
- Heat Sentry[™] automatically turns blower to high speed when excess cooking heat is detected
- Fully enclosed bottom
- Power supply cord included
- One Year Limited Warranty
- Recommended for use with Models LB30, LB36, LT30, and LT36 Liners
- Title 24 compliant
- **OPTIONAL ACCESSORIES:**
- Model 357NDK Non-ducted recirculating kit (includes charcoal filter, soffit grille, 90° stack boot, and 6" to 7" round transition)
- Disposable charcoal filter kit part no. B08999040

SPECIFICATIONS

	VOLTS	AMPS	CFM	SONES	DUCT
High Speed	120	2.9	390	6.0	6-in. round
Working Speed	120		240	2.5	6-in. round

Note: High Speed air and sound specifications are HVI Certified.

Broan-NuTone LLC certifies that Working Speed air and sound values result from tests conducted according to HVI Procedures.

> Broan-NuTone LLC Hartford, Wisconsin www.broan.com 800-558-1711 www.nutone.com 888-336-3948 Broan-NuTone Canada Mississauga, Ontario www.broan.ca

the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

HVI-2100 CERTIFIED RATINGS comply with new testing

technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are

available to consumers. Product performance is rated at 0.1

in. static pressure, based on tests conducted in a state-of-

w.nutone.com	000-000-0
877-896-1119	

		U		
REFERENCE	QTY.	REMARKS	Project	
			Location	
			Architect	
			Engineer	
			Contractor	
			Submitted by	Date

TYPICAL SPECIFICATION

Power Pack shall be Broan® (NuTone®) Model PM390.

Power Pack shall have a multi-speed fan switch and separate light switch.

Fan must be convertible between ducted and nonducted discharge. Ducted mode uses a washable aluminum mesh filter. Non-ducted mode uses optional, disposable charcoal filter.

Unit shall have a durable, powder coated finish.

Air delivery to be at least 390 CFM and sound levels not greater than 6.0 Sones.

Unit shall be UL and cUL listed.



